

INDUSTRIAL VALVE & ENGINEERING SUPPLIES VALVE & ENGINEERING MERCHANT COMPANY

BMC
VALVE

Break Away
Brand Valves

FIG 2302

BREAKAWAY SAFETY VALVE

FEATURES

Trim: REPLACEABLE SILICONE SEAL TRIM
B.S.P THREADS TO BS 21 TAPER
MANUFACTURED IN SOUTH AFRICA

WORKING PRESSURE (BAR) NON SHOCK

MAX WORKING PRESSURE NON SHOCK		HYDROSTATIC TEST PRESSURE	
MAX STEAM	NOT SUITABLE	SHELL	SEAT
MAX W.O.G.	8 BAR @ 0 TO 200 DEG C	28 BAR	10 BAR



Valves can be set on request



ITEM	SPECIFICATION
BODY	BR-BS2872
SEAT	BR-BS2872
CLACK	Silicone
ADJUSTING SCREW	BR-BS2872
LOCK NUT	BR-BS2872
SPINDLES	BR-BS2872
RING	CHROMED M/S
SPRING	SS-GR304

SIZE BSP	L	H	MASS grams
8	78	56	45
10	78	60	65
15	78	65	120

SPRING RANGE		
LIGHT	SILVER	0-200 KPA
MEDIUM	GOLD	100-1000 KPA
HEAVY	BLUE	750-1750 KPA
X-HEAVY	RED	1500-2500 KPA

All Specifications are subject to change without notice

Head Office:

+27-11-394-2066 (21 Lines)
sales@industrialvalve.co.za
www.industrialvalve.co.za
114 Plane Road
Spartan
Gauteng
South Africa

KZN Branch:

+27-31-205-0218
laven@industrialvalve.co.za
www.industrialvalve.co.za
Unit No 16 5-29
Eaton Road
Congella
Durban

Cape Town Branch:

+27-21-982-0302
ivesct@industrialvalve.co.za
www.industrialvalve.co.za
Unit 14 Silver Park
Silver Street
Brackenfell
Cape Town